



হিরোর দেশ
বাংলাদেশ



3D BRANDING



USB CHARGER



i3S TECHNOLOGY



NEW
GLAMOUR
SIMPLY MAGNETIC

SPECIFICATIONS

ENGINE	
Type	Air cooled, 4 - stroke single cylinder OHC
Displacement	124.7 cc
Maximum Power	6.72 kW (9.1 Ps) @7000 rpm
Maximum Torque	10.35 N-m @4000 rpm
Bore x Stroke	52.4 x 57.8 mm
Compression Ratio	9.1:1
Starting	Self Start / Kick Start
TRANSMISSION	
Clutch	Multiplate wet
Gear box	4 - speed constant mesh
Chassis Type	Tubular Double Cradle Type
SUSPENSION	
Front	Telescopic Hydraulic Shock Absorbers
Rear	Rectangular swing arm with 5-step adjustable Hydraulic Shock Absorbers
BRAKES	
Front	Disc
	Drum
	240 mm Dia; Pad - Non Asbestos type Internal expanding shoe type - 130 mm Liners - Non Asbestos type
Rear	Drum
	Internal expanding shoe type - 130 mm Liners - Non Asbestos type
TYRES	
Tyre Size	Front 80/100 - 18", Tubeless Rear 80/100 - 18", Tubeless

ELECTRICALS	
Battery	12 V - 3 Ah MF Battery
Head Lamp	12 V - 35 W / 35 W - Halogen Bulb (Multi-Reflector Type)
Tail / Stop Lamp	12 V - 5 / 21 W (Multi-Reflector)
Turn Signal Lamp	12 V - 10 W (Amber Bulb) x 4 nos (MFR - Clear Lens)
Engine Oil Grade	SAE 10W 30 SL Grade (JASO MA2)
Fuel Tank Capacity	13 Ltrs.
Reserve	1.4 litres (Usable Reserve)
DIMENSIONS	
LxWxH	2008 X 768 X 1080 mm
Wheelbase	1264 mm
Ground clearance	160 mm
WEIGHT	
Kerb weight	127 kgs (self)

DIGI-ANALOG METER CONSOLE



BS4 ENGINE



TUBELESS TYRE



COLOR AVAILABLE



Techno Blue



Candy Blazing Red



NILOY MOTORS LIMITED

(Sole Distributor of Hero Motorcy)
Nito-Nilo Tower, 69 Nikunja-2 C/A
Khilkhet, Dhaka-1229
Phone: 09363 666 666, 01905 999 222

HMCL NILOY BANGLADESH LIMITED

(Joint Venture of Hero MotoCorp Ltd, India & Niloy Motors Ltd, Bangladesh)
Nitol Niloy Tower, Plot-69 Nikunja-2, Khilkhet, Dhaka-1229, Bangladesh.
www.heromotocorp.com/bd