

THRILLER 160R

RIDE THE FUTURE

0-60KM/H IN 4.7SECS



INVERTED **FULL DIGITAL**
METER CONSOLE

REDEFINED AGGRESSION



EXTENDED GRAB RAIL



AGGRESSIVE GRAPHICS



SPORTY BELLY PAN



USB CHARGING PORT

THRILLER 160R

RIDE THE FUTURE



SPECIFICATIONS

ENGINE

ENGINE TYPE	AIR COOLED, 4 STROKE 2 VALVE SINGLE CYLINDER OHC
DISPLACEMENT	163 cc
MAX POWER	11.2 kw (15 bhp) @ 8500 revolutions per minute
MAX TORQUE	14 Nm @ 6500 revolutions per minute
FUEL SYSTEM	ADVANCED PROGRAMMED FUEL INJECTION
STARTING	SELF & KICK

TRANSMISSION & CHASSIS

CLUTCH	MULTI PLATE WET CLUTCH
GEARBOX	5 SPEED CONSTANT MESH
FRAME TYPE	TUBULAR DIAMOND

SUSPENSION

FRONT	TELESCOPIC (37 mm DIA) WITH ANTI FRICTION BUSH
REAR	7 STEP RIDER-ADJUSTABLE MONOSHOCK

BRAKES

FRONT BRAKE TYPE	276 mm PETAL DISC, SINGLE CHANNEL ABS
REAR BRAKE TYPE	220 mm PETAL DISC 130 mm DRUM

TYRES

FRONT TYRE	100/80-17 (TUBELESS)
REAR TYRE	130/70 -R17 RADIAL (TUBELESS)

ELECTRICALS

SPEEDOMETER	INVERTED LCD CONSOLE
HEAD LIGHT	FULL LED WITH LED DRLS

DIMENSIONS

LENGTH X WIDTH X HEIGHT	2029 X 793 X 1052 mm
WHEELBASE	1327 mm
SEAT HEIGHT	795 mm
GROUND CLEARANCE	165 mm

WEIGHTS

KERB WEIGHT	139.5 kg 138.5 kg
FUEL TANK CAPACITY	12 Litre

#Figures highlighted in red indicate specification for Double Disc variant

AVAILABLE IN ATTRACTIVE COLOURS



SPORTS RED

PEARL SILVER WHITE

VIBRANT BLUE



NILOY MOTORS LIMITED

(Sole Distributor of Hero Motorcycle)

Nitol-Niloy Tower, Plot-69, Nikunja-2 C/A, Khilkhet, Dhaka-1229, Bangladesh.
E-mail: corporate@niloymotors.com | Phone: 09636 666 666

HMCL NILOY BANGLADESH LIMITED

(Joint Venture of Hero Moto Corp Ltd, India & Niloy Motors Ltd, Bangladesh)

Nitol-Niloy Tower, Plot-69, Nikunja-2 C/A, Khilkhet, Dhaka-1229, Bangladesh.
www.heromotocorp.com/bd



*Conditions apply.